



JDYX.E10480 Fuses, Supplemental

Page Bottom

Fuses, Supplemental

See General Information for Fuses, Supplemental

LITTELFUSE INC

E10480

SUITE 500
8755 W HIGGINS RD
CHICAGO, IL 60631 USA

Supplemental fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
373*+, followed by 12 thru 15.				
	6.35 x 31.75 (0.25 x 1.25)	12 - 15	125Vac	10000

Supplemental fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
312	6.35 x 31.75 (0.25 x 1.25)	12	32Vdc	300
		15 - 25	32Vdc	300
		12	32Vac	300
		15 - 25	32Vac	300
318	6.35 x 31.75 (0.25 x 1.25)	15 - 25	32Vac	300
		15 - 25	32Vdc	300
		12	32Vdc	300
		12	32Vac	300
375*+, followed by 12 thru 15.				
	6.35 x 31.75 (0.25 x 1.25)	12 - 15	125Vac	10000

Supplemental fuses: pigtail leads, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
224*+, followed by 0.1 thru 3.5; WP90736, followed by List 01 thru 11, 101 thru 111.				
	4.5 x 15 (0.18 x 0.59)	0.1 - 0.25	125Vdc	10000
		0.1 - 0.25	125Vac	10000
		0.1 - 0.25	250Vac	35

		0.375 - 1.0	125Vac	10000
		0.375 - 1.0	250Vac	35
		0.375 - 1.0	125Vdc	10000
		1.5 - 3.5	125Vdc	10000
		1.5 - 3.5	125Vac	10000
		1.5 - 3.5	250Vac	100
230*+, followed by 0.25 thru 3; WP90904, followed by List 01 thru 10, 101 thru 110.				
	4.5 x 15.5 (0.18 x 0.61)	0.25 - 3.5	125Vac	10000
		0.25 - 3.5	125Vdc	10000
		0.25 - 1.0	250Vac	35
		1.1 - 3.5	250Vac	100
		0.25 - 3.0	310Vac	80
235xxxE*+, 235xxxSP*+, followed by 0.1 thru 7.				
	5 x 20 (0.20 x 0.79)	0.1 - 0.8	250Vac	35
		0.1 - 0.8	125Vac	10000
		1.0 - 3.5	250Vac	100
		1.0 - 7.0	125Vac	10000
236*+, followed by 0.1 thru 7.				
	5 x 20 (0.20 x 0.79)	0.1 - 0.8	250Vac	35
		0.1 - 0.8	125Vac	10000
		1.0 - 3.5	250Vac	100
		1.0 - 7.0	125Vac	10000
239xxxE*+, 239xxxSP*+ followed by 4 thru 7.				
	5 x 20 (0.20 x 0.79)	4.0 - 7.0	125Vac	10000
318*+	6.35 x 31.75 (0.25 x 1.25)	0.01 - 0.3	125Vac	10000
		0.01 - 0.3	250Vac	35
		0.375 - 0.75	125Vac	10000
		0.375 - 0.75	250Vac	35
		1.0 - 3.5	125Vac	10000
		1.0 - 3.5	250Vac	100
		3.6 - 10	125Vac	10000
		3.6 - 10	250Vac	200
375*+, followed by 4 thru 10.				
	6.35 x 31.75 (0.25 x 1.25)	4.0 - 10	250Vac	200
		4.0 - 10	125Vac	10000
62NM	6.35 x 31.8 (0.25 x 1.25)	0.032 - 0.315	125Vac	10000
		0.032 - 0.315	250Vac	35
		0.4 - 1.0	125Vac	10000

		0.4 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3.0 - 5.0	125Vac	10000
		3.0 - 5.0	250Vac	200
		6.0 - 10	125Vac	10000
		6.0 - 10	250Vac	200
625	6.85 x 33 (0.27 x 1.30)	0.032 - 0.315	125Vac	10000
		0.032 - 0.315	250Vac	35
		0.35 - 1.0	125Vac	10000
		0.35 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3.0 - 3.5	125Vac	10000
		3.0 - 3.5	250Vac	100
		4.0 - 5.0	125Vac	10000
		4.0 - 5.0	250Vac	200

Supplemental fuses: pigtail leads, filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
324, followed by 0.125 thru 15				
	6.35 x 31.75 (0.25 x 1.25)	0.125 - 0.75	125Vac	10000
		0.125 - 0.75	250Vac	35
		1 - 3	125Vac	10000
		1 - 3	250Vac	100
		15	125Vac	10000
		15	250Vac	750
		4 - 6	125Vac	10000
		4 - 6	250Vac	750
		7 - 12	125Vac	10000
		7 - 12	250Vac	750
		0.125 - 0.75	125Vdc	10000
		1 - 3	125Vdc	10000
		4 - 6	125Vdc	10000
		7 - 12	125Vdc	10000
		15	125Vdc	10000
325*+, followed by 0.25 thru 10; WP91769, followed by List 01 thru 34.				
	6.35 x 31.75 (0.25 x 1.25)	0.25 - 3.5	250Vac	100
		4.0 - 6.25	250Vac	400

	0.25 - 3.5	125Vac	10000
	4.0 - 6.25	125Vac	10000
	7.0 - 10	125Vac	10000
	7.0 - 10	250Vac	400
	0.25 - 3.0	125Vdc	10000
	7.0 - 10	125Vdc	10000
	4.0 - 6.25	125Vdc	10000

Supplemental fuses: pigtail leads, time delay, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
239xxxE*+, 239xxxSP*+ followed by 0.08 thru 3.5.				
	5 x 20 (0.20 x 0.79)	0.08 - 1.0	250Vac	35
		1.25 - 3.5	250Vac	100
		0.08 - 3.5	125Vac	10000
315*+, followed by 0.01 thru 10.				
	6.35 x 31.75 (0.25 x 1.25)	0.01 - 0.15	125Vac	10000
		0.01 - 0.15	250Vac	35
		0.175 - 1.0	250Vac	35
		1.2 - 3.2	250Vac	100
		10	125Vac	10000
		10	250Vac	200
		0.175 - 1.0	125Vac	10000
		1.2 - 3.2	125Vac	10000
		4 - 8	125Vac	10000
		4 - 8	250Vac	200

Supplemental fuses: cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
220*+, followed by 001, 002, 003, 004, 006, 011 or 029; WP90400, followed by List 1, 4 or 6; WP90109, followed by List 1.				
	4.5 x 15.5 (0.18 x 0.61)	0.35	250Vac	35
		0.35	125Vac	10000
220010*+	4.5 x 15.5 (0.18 x 0.61)	0.55	250Vac	35
		0.55	125Vac	10000
		0.55	125Vdc	10000
220018*+	4.5 x 15 (0.18 x 0.59)	3	250Vac	100
		3	125Vac	10000
		3	125Vdc	10000

220024*+	4.5 x 15.5 (0.18 x 0.61)	1	250Vac	35
		1	125Vac	10000
		1	125Vdc	10000
220025*+	4.5 x 15.5 (0.18 x 0.61)	1.25	250Vac	100
		1.25	125Vac	10000
		1.25	125Vdc	10000
220026*+	4.5 x 15.5 (0.18 x 0.61)	1.5	250Vac	100
		1.5	125Vac	10000
		1.5	125Vdc	10000
220030*+	4.5 x 15.5 (0.18 x 0.61)	0.375	250Vac	35
		0.375	125Vac	10000
		0.375	125Vdc	10000
220031*+	4.5 x 15 (0.18 x 0.59)	0.3	250Vac	35
		0.3	125Vac	10000
		0.3	125Vdc	10000
220033*+	4.5 x 15.5 (0.18 x 0.61)	1.5	250Vac	100
		1.5	125Vac	10000
		1.5	125Vdc	10000
220036*+	4.5 x 15 (0.18 x 0.59)	0.5	300Vac	35
		0.5	125Vac	10000
220043*+	4.5 x 15.5 (0.18 x 0.61)	1.0	250Vac	35
		1.0	125Vac	10000
		1.0	125Vdc	10000
220056*+, 220057*+	4.5 x 15.5 (0.18 x 0.61)	1.25	250Vac	100
		1.25	125Vac	10000
		1.25	125Vdc	10000
225*+, followed by 0.1 thru 3.5				
	4.5 x 15 (0.18 x 0.59)	0.1 - 0.25	125Vdc	10000
		0.1 - 0.25	125Vac	10000
		0.1 - 0.25	250Vac	35
		0.375 - 1.0	125Vac	10000
		0.375 - 1.0	250Vac	35
		0.375 - 1.0	125Vdc	10000
		1.5 - 3.5	125Vdc	10000
		1.5 - 3.5	125Vac	10000
		1.5 - 3.5	250Vac	100

229*+ , followed by 0.25 thru 3.5				
	4.5 x 15.5 (0.18 x 0.61)	0.25 - 3.5	125Vac	10000
		0.25 - 3.5	125Vdc	10000
		0.25 - 1.0	250Vac	35
		1.1 - 3.5	250Vac	100
		0.25 - 3.0	310Vac	80
233*+ , followed by 1 thru 10.				
	5 x 20 (0.20 x 0.79)	1 - 6.3	125Vac	10000
		7 - 10	125Vac	10000
234*+ , followed by 1 thru 10.				
	5 x 20 (0.20 x 0.79)	1 - 3.5	250Vac	100
		1 - 3.5	125Vac	10000
		4 - 10	250Vac	200
		4 - 10	125Vac	10000
235*+ , followed by 0.1 thru 7.				
	5 x 20 (0.20 x 0.79)	0.1 - 0.8	250Vac	35
		0.1 - 0.8	125Vac	10000
		1.0 - 3.5	250Vac	100
		1.0 - 7.0	125Vac	10000
237*+ , followed by 1 thru 10.				
	5 x 20 (0.20 x 0.79)	1 - 2.5	125Vac	10000
		3 - 10	125Vac	10000
239*+ followed by 4 thru 7.				
	5 x 20 (0.20 x 0.79)	4.0 - 7.0	125Vac	10000
300154* , 309001* , 309001.5*				
	6.35 x 15.88 (0.25 x 0.63)	1 - 1.5	125Vac	-
310278*	6.35 x 31.75 (0.25 x 1.25)	3	250Vac	35
		3	125Vac	10000
310279*	6.35 x 31.75 (0.25 x 1.25)	7	125Vac	10000
		7	250Vac	200
310306*	6.35 x 31.75 (0.25 x 1.25)	7	125Vac	10000
		7	250Vac	200
312*+	6.35 x 31.75 (0.25 x 1.25)	0.01 - 0.3	125Vac	10000
		0.01 - 0.3	250Vac	35
		0.375 - 0.75	125Vac	10000
		0.375 - 0.75	250Vac	35

		1.0 - 3.5	125Vac	10000
		1.0 - 3.5	250Vac	100
		3.6 - 10	125Vac	10000
		3.6 - 10	250Vac	200
373*+, followed by 4 thru 10.				
	6.35 x 31.75 (0.25 x 1.25)	4.0 - 10	125Vac	10000
		4.0 - 10	250Vac	200
61NM	6.35 x 31.8 (0.25 x 1.25)	0.032 - 0.315	125Vac	10000
		0.032 - 0.315	250Vac	35
		0.4 - 1.0	125Vac	10000
		0.4 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3.0 - 5.0	125Vac	10000
		3.0 - 5.0	250Vac	200
		6.0 - 10	125Vac	10000
		6.0 - 10	250Vac	200
61S	6.35 x 31.8 (0.25 x 1.25)	0.032 - 0.315	125Vac	10000
		0.032 - 0.315	250Vac	35
		0.35 - 1.0	125Vac	10000
		0.35 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3.0 - 3.5	125Vac	10000
		3.0 - 3.5	250Vac	100
		4.0 - 5.0	125Vac	10000
		4.0 - 5.0	250Vac	200
KLKD*, folowed by 0.1 thru 30, may be followed by R.				
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.5	600Vac	10000
		0.1 - 0.5	600Vac	25000
		0.1 - 0.5	600Vac	50000
		0.1 - 0.5	600Vac	100000
		0.75 - 1.5	600Vac	10000
		0.75 - 1.5	600Vac	25000
		0.75 - 1.5	600Vac	50000
		0.75 - 1.5	600Vac	100000
		2.0 - 12	600Vac	10000
		2.0 - 12	600Vac	25000
		2.0 - 12	600Vac	50000

2.0 - 12	600Vac	100000
15 - 30	600Vac	10000
15 - 30	600Vac	25000
15 - 30	600Vac	50000
15 - 30	600Vac	100000
0.1 - 0.5	600Vdc	10000
0.1 - 0.5	600Vdc	25000
0.1 - 0.5	600Vdc	50000
0.75 - 1.5	600Vdc	10000
0.75 - 1.5	600Vdc	25000
0.75 - 1.5	600Vdc	50000
2.0 - 12	600Vdc	10000
2.0 - 12	600Vdc	25000
2.0 - 12	600Vdc	50000
15 - 30	600Vdc	10000
15 - 30	600Vdc	25000
15 - 30	600Vdc	50000

Supplemental fuses: filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)	
310296*	6.35 x 31.75 (0.25 x 1.25)	15	250Vac	750	
		15	125Vac	10000	
310299*	6.35 x 31.75 (0.25 x 1.25)	10	250Vac	750	
		10	125Vac	10000	
314 , followed by 0.125 thru 15					
	6.35 x 31.75 (0.25 x 1.25)	0.125 - 0.75	250Vac	35	
		0.125 - 0.75	125Vac	10000	
		1 - 3	250Vac	100	
		1 - 3	125Vac	10000	
		15	125Vac	10000	
		15	250Vac	750	
		4 - 6	125Vac	10000	
		4 - 6	250Vac	750	
		7 - 12	125Vac	10000	
		7 - 12	250Vac	750	
		0.125 - 0.75	125Vdc	10000	
		1 - 3	125Vdc	10000	
		4 - 6	125Vdc	10000	
		7 - 12	125Vdc	10000	

	15	125Vdc	10000	
326*+, followed by 0.25 thru 10; WP91769, followed by List 101 thru 134.				
6.35 x 31.75 (0.25 x 1.25)	0.25 - 3.5	250Vac	100	
	0.25 - 3.5	125Vac	10000	
	4.0 - 6.25	125Vac	10000	
	7.0 - 10	125Vac	10000	
	4.0 - 6.25	250Vac	400	
	7.0 - 10	250Vac	400	
	0.25 - 3.0	125Vdc	10000	
	7.0 - 10	125Vdc	10000	
	4.0 - 6.25	125Vdc	10000	
519, folowed by 0.1 thru 30, may be followed by R.				
10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.5	600Vac	10000	
	0.1 - 0.5	600Vac	25000	
	0.1 - 0.5	600Vac	50000	
	0.1 - 0.5	600Vac	100000	
	0.75 - 1.5	600Vac	10000	
	0.75 - 1.5	600Vac	25000	
	0.75 - 1.5	600Vac	50000	
	0.75 - 1.5	600Vac	100000	
	2.0 - 12	600Vac	10000	
	2.0 - 12	600Vac	25000	
	2.0 - 12	600Vac	50000	
	2.0 - 12	600Vac	100000	
	15 - 25	600Vac	10000	
	15 - 25	600Vac	25000	
	15 - 25	600Vac	50000	
	15 - 25	600Vac	100000	
	30	600Vac	10000	
	30	600Vac	25000	
	30	600Vac	50000	
	30	600Vac	100000	
	0.1 - 0.5	600Vdc	10000	
	0.1 - 0.5	600Vdc	25000	
	0.1 - 0.5	600Vdc	50000	
	0.75 - 1.5	600Vdc	10000	
	0.75 - 1.5	600Vdc	25000	
	0.75 - 1.5	600Vdc	50000	
	2.0 - 12	600Vdc	10000	
	2.0 - 12	600Vdc	25000	

		2.0 - 12	600Vdc	50000
		15 - 25	600Vdc	10000
		15 - 25	600Vdc	25000
		15 - 25	600Vdc	50000
		30	600Vdc	10000
		30	600Vdc	25000
		30	600Vdc	50000
532, followed by 0.1 thru 30.				
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.5	600Vac	10000
		0.1 - 0.5	600Vac	25000
		0.1 - 0.5	600Vac	50000
		0.1 - 0.5	600Vac	100000
		0.75 - 1.5	600Vac	10000
		0.75 - 1.5	600Vac	25000
		0.75 - 1.5	600Vac	50000
		0.75 - 1.5	600Vac	100000
		2.0 - 12	600Vac	10000
		2.0 - 12	600Vac	25000
		2.0 - 12	600Vac	50000
		2.0 - 12	600Vac	100000
		15 - 25	600Vac	10000
		15 - 25	600Vac	25000
		15 - 25	600Vac	50000
		15 - 25	600Vac	100000
		30	600Vac	10000
		30	600Vac	25000
		30	600Vac	50000
		30	600Vac	100000
65TS	6.35 x 31.8 (0.25 x 1.25)	1	125Vac	10000
		1	250Vac	35
		1.1 - 3.5	125Vac	10000
		1.1 - 3.5	250Vac	100
		3.6 - 7	125Vac	10000
		3.6 - 7	250Vac	200
		8 - 10	125Vac	10000
		8 - 10	250Vac	200
		10.1 - 15	125Vac	10000
		10.1 - 15	250Vac	750
EV60030	10.32 x 38.1 (0.41 x 1.50)	30	600Vdc	10000
		30	600Vdc	25000

	30	600Vdc	50000	
	30	600Vac	10000	
	30	600Vac	25000	
	30	600Vac	50000	
	30	600Vac	100000	
F60C, followed by 0.1 thru 30.				
10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.5	500Vac	100000	
	0.75 - 1.5	500Vac	100000	
	2.0 - 12	500Vac	100000	
	15 - 25	500Vac	100000	
	30	500Vac	100000	
	0.1 - 0.5	500Vdc	100000	
	0.75 - 1.5	500Vdc	100000	
	2.0 - 12	500Vdc	100000	
	15 - 25	500Vdc	100000	
	30	500Vdc	100000	
	KLK*, followed by 0.1 thru 30.			
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.5	600Vac	10000
		0.1 - 0.5	600Vac	25000
		0.1 - 0.5	600Vac	50000
0.1 - 0.5		600Vac	100000	
0.75 - 1.5		600Vac	10000	
0.75 - 1.5		600Vac	25000	
0.75 - 1.5		600Vac	50000	
0.75 - 1.5		600Vac	100000	
2.0 - 12		600Vac	10000	
2.0 - 12		600Vac	25000	
2.0 - 12		600Vac	50000	
2.0 - 12		600Vac	100000	
15 - 25		600Vac	10000	
15 - 25		600Vac	25000	
15 - 25		600Vac	50000	
15 - 25		600Vac	100000	
30		600Vac	10000	
30		600Vac	25000	
30		600Vac	50000	
30		600Vac	100000	
0.1 - 0.5		500Vdc	50000	
0.75 - 1.5		500Vdc	50000	
2.0 - 12		500Vdc	50000	

		15 - 25	500Vdc	50000
		30	500Vdc	50000
KLQ, followed by 1 thru 6.				
	10.32 x 38.1 (0.41 x 1.50)	1.0 - 3.0	600Vac	10000
		5.0 - 6.0	600Vac	10000
LGR*, followed by 0.5 thru 15. (w. knob)				
	6.35 x 46.23 (0.25 x 1.82)	0.5 - 1.6	300Vdc	10000
		2 - 7	300Vdc	10000
		8 - 15	300Vdc	10000
LMF*, followed by 0.3 thru 10. (w. knob)				
	6.35 x 46.23 (0.25 x 1.82)	0.3 - 1.25	300Vac	10000
		1.6 - 10	300Vac	10000
WP91768, followed by List 1 thru 16, 101 thru 116.				
	6.35 x 31.75 (0.25 x 1.25)	0.125 - 0.75	125Vac	10000
		0.125 - 0.75	250Vac	35
		1 - 3	125Vac	10000
		1 - 3	250Vac	100
		15	125Vac	10000
		15	250Vac	750
		4 - 6	125Vac	10000
		4 - 6	250Vac	750
		7 - 12	125Vac	10000
		7 - 12	250Vac	750
		0.125 - 0.75	125Vdc	10000
		1 - 3	125Vdc	10000
		4 - 6	125Vdc	10000
		7 - 12	125Vdc	10000
		15	125Vdc	10000

Supplemental fuses: paper tube, filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
530 or FLA*, followed by 0.1 thru 30.				
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 2.5	125Vac	10000
		2.8 - 10	125Vac	10000
		12 - 30	125Vac	10000
535 or BLN*, followed by 0.5 thru 30; WP91770, followed by List 1 thru 13.				
	10.32 x 38.1 (0.41 x 1.50)	0.5 - 5	250Vac	10000
		5.5 - 7	250Vac	10000

		8 - 15	250Vac	10000
		20	250Vac	10000
		25 - 30	250Vac	10000
536 or BLF*, followed by 0.5 thru 15.				
	10.32 x 38.1 (0.41 x 1.50)	0.5 - 5	250Vac	10000
		5.5 - 7	250Vac	10000
		8 - 15	250Vac	10000
536 or BLF*, followed by 20 thru 30.				
	10.32 x 38.1 (0.41 x 1.50)	20.0 - 30.0	125Vac	10000
537 or BLS*, followed by 0.2 thru 10.				
	10.32 x 34.93 (0.41 x 1.38)	0.2 - 1.8	600Vac	10000
		4 - 5	600Vac	10000
		1 - 3	600Vac	10000
		6.0 - 10	250Vac	10000

Supplemental fuses: time delay, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
239*+ followed by 0.08 thru 3.5.				
	5 x 20 (0.20 x 0.79)	0.08 - 1.0	250Vac	35
		1.25 - 3.5	250Vac	100
		0.08 - 3.5	125Vac	10000
313*+ or 313ID*+, followed by 0.01 thru 10.				
	6.35 x 31.75 (0.25 x 1.25)	0.01 - 0.15	250Vac	35
		0.01 - 0.15	125Vac	10000
		0.175 - 1.0	250Vac	35
		1.2 - 3.2	250Vac	100
		10	125Vac	10000
		10	250Vac	200
		0.175 - 1.0	125Vac	10000
		1.2 - 3.2	125Vac	10000
		4 - 8	125Vac	10000
		4 - 8	250Vac	200

Supplemental fuses: time delay, filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
533 or FLM*, followed by 0.1 thru 30.				
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 7	250Vac	10000

	8 - 10	250Vac	10000
	12 - 30	250Vac	10000

Supplemental fuses: time delay, paper tube, filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
538 or FLQ*, followed by 0.1 thru 30, may be followed by HXR.				
	10.32 x 38.1 (0.41 x 1.50)	0.1 - 0.2	500Vac	10000
		0.25 - 7	500Vac	10000
		8 - 9	500Vac	10000
		10 - 12	500Vac	10000
		14 - 15	500Vac	10000
		16 - 30	500Vac	10000

Supplemental micro fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
428	-	0.033 - 0.05	125Vac	50
		0.063 - 0.160	125Vac	50
		0.033 - 0.05	72Vdc	50
		0.063 - 0.160	72Vdc	50
450011MR	2.16 x 5.97 (0.09 x 0.24)	0.062 - 0.1	125Vdc	50
		0.062 - 0.1	125Vac	50
		0.062 - 0.1	32Vdc	300
		0.125 - 0.315	125Vdc	50
		0.125 - 0.315	125Vac	50
		0.125 - 0.315	32Vdc	300
		0.375 - 1.0	125Vdc	50
		0.375 - 1.0	125Vac	50
		0.375 - 1.0	32Vdc	300
		1.25 - 1.6	125Vdc	50
		1.25 - 1.6	125Vac	50
		1.25 - 1.6	32Vdc	300
		2.0 - 5.0	125Vdc	50
		2.0 - 5.0	125Vac	50
		2.0 - 5.0	32Vdc	300
		2.0 - 5.0	75Vdc	1000
451 \$	2.16 x 5.97 (0.09 x 0.24)	0.062 - 0.1	125Vdc	50
		0.062 - 0.1	125Vac	50
		0.062 - 0.1	32Vdc	300
		0.125 - 0.315	125Vdc	50

		0.125 - 0.315	125Vac	50
		0.125 - 0.315	32Vdc	300
		0.375 - 1.0	125Vdc	50
		0.375 - 1.0	125Vac	50
		0.375 - 1.0	32Vdc	300
		1.25 - 1.6	125Vdc	50
		1.25 - 1.6	125Vac	50
		1.25 - 1.6	32Vdc	300
		2.0 - 5.0	125Vdc	50
		2.0 - 5.0	125Vac	50
		2.0 - 5.0	32Vdc	300
		2.0 - 5.0	75Vdc	10000
453	2.16 x 5.97 (0.09 x 0.24)	0.062 - 0.1	125Vdc	50
		0.062 - 0.1	125Vac	50
		0.062 - 0.1	32Vdc	300
		0.125 - 0.315	125Vdc	50
		0.125 - 0.315	125Vac	50
		0.125 - 0.315	32Vdc	300
		0.375 - 1.0	125Vdc	50
		0.375 - 1.0	125Vac	50
		0.375 - 1.0	32Vdc	300
		1.25 - 1.6	125Vdc	50
		1.25 - 1.6	125Vac	50
		1.25 - 1.6	32Vdc	300
		2.0 - 5.0	125Vdc	50
		2.0 - 5.0	125Vac	50
		2.0 - 5.0	32Vdc	300
		2.0 - 5.0	75Vdc	1000
490	2.16 x 5.97 (0.09 x 0.24)	0.062 - 0.1	125Vdc	50
		0.062 - 0.1	125Vac	50
		0.062 - 0.1	32Vdc	300
		0.125 - 0.315	125Vdc	50
		0.125 - 0.315	125Vac	50
		0.125 - 0.315	32Vdc	300
		0.375 - 1.0	125Vdc	50
		0.375 - 1.0	125Vac	50
		0.375 - 1.0	32Vdc	300
		1.25 - 1.6	125Vdc	50
		1.25 - 1.6	125Vac	50
		1.25 - 1.6	32Vdc	300

	2.0 - 5.0	125Vdc	50
	2.0 - 5.0	125Vac	50
	2.0 - 5.0	32Vdc	300
	2.0 - 5.0	75Vdc	1000

Supplemental micro fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
874	3.6 x 10 (0.14 x 0.39)	0.1 - 0.2	250Vac	50
		0.25 - 0.4	250Vac	50
		0.5 - 0.8	250Vac	50
		1.0 - 10	250Vac	50
875	3.6 x 10 (0.14 x 0.39)	12	125Vac	50
		12	32Vdc	50
		0.1 - 0.3	250Vac	50
		0.4 - 2.0	250Vac	50
		2.5 - 5.0	250Vac	50
		6.0 - 10	250Vac	50

\$ - May be followed by -L or -SN.

(a) - Followed by .500, 001, 01.5, 002, 02.5 or 3.15, may have one prefix and may have up to three additional suffix letters. The prefix or suffix serve as options such as packaging, etc. and do not affect the electrical characteristics.

* - With or without prefix characters and with or without additional suffix characters that signify options such as packaging, etc. and do not affect the electrical characteristics.

+ - May be followed by P indicating using lead free solder.

Last Updated on 2014-04-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".